



V A R C O P R U D E N B U I L D I N G S

## TEXTURECLAD™ WALL PANEL

WALL SYSTEMS



### FEATURES

- Easy installation with concealed fasteners
- Tongue and groove fit
- 16" width coverage; lengths up to 30'
- 20 year warranty
- 24 standard colors (custom colors available)
- 20 ga. panel with 24 and 20 ga. trims
- Durable stucco finish

### BENEFITS

- TextureClad provides the appearance of stucco without the additional cost
- Works great as a soffit panel
- Great alternative when covenants restrict use of metal panel appearance
- Lightweight and stackable, ideal for applications up to six stories
- Can be installed over hat channels to achieve thicker insulation and higher R-values

# TEXTURECLAD™ WALL PANEL

An interlocking architectural metal wall panel system with the rich texture of stucco

The stucco-like appearance of TextureClad will satisfy most local building ordinances that prohibit other metal wall panel applications. These panels are durable and provide protection from ultraviolet rays.

Each TextureClad panel is manufactured from 20-gauge galvanized steel. Panel width installed is 16". Both top and bottom of every panel has a 5/8" fold back. Formed ends allow the panel to rest end-to-end for stacking on a vertical wall, allowing for applications up to six stories. Panel lengths range from 14" to 30'.

Primed on both sides, the baked-on base coat is specifically formulated to adhere to the textured finish. Factory applied textured finish is a proprietary formula. The finish is resistant to water, cracking, chalking, mildew and loss of adhesion.

The panels are available in a wide selection of standard colors, ask for VP color guide #6023. Custom colors are available upon request. TextureClad comes with a 20-year warranty for the panel and finish. Installation guides are available.


- Panel Width: 16" coverage
- Panel Depth: 7/8"
- Panel Length: Min. 14" Max. 30'
- Gauges: 20 gauge
- Substrate: G90 Galvanized
- Exterior Coating: Baked-on stucco-like proprietary acrylic formulation with synthetic aggregate
- Interior Coating: Standard epoxy coating
- Ext. Coat Warranty: 20 yrs.
- Finish: Stucco-like
- Profile: Textured embossed
- Other options: 5/8" fold back top and bottom

For information about this or any other VP product or service, contact your local authorized VP Builder.

*Note: All panels formed from light gauge metal may exhibit waviness, also known as "Oil Canning," commonly occurring in, but not restricted to, flat portions of a panel. This inherent characteristic is not a defect of material or manufacturing and is not cause for rejection.*



## TEXTURECLAD WALL PROFILE



CHARACTERISTICS	TEST METHOD
Air Infiltration	ASTM E283-91
Base Metal (hot dipped galvanized)	ASTM A924
Coating Film Hardness	ASTM 3363
Color Retention <i>Does not show color change at 2000 hours</i>	ASTM G7-05
Flammability	ASTM E-84
Florida Approval*	FL 12906
Impact Resistance*	Miami-Dade County NOA 15-0915.13 NOA 15-0915.14
Racking Shear	ASTM E72-80
Salt Spray	ASTM B-117
Structural	ASTM E1592
Water Penetration	ASTM E331-86
Water Soak	ASTM D870
Weathering	ASTM G7-05

\*Requires special clips that are available in addition to VP's standard product offering.



Varco Pruden Buildings, 3200 Players Club Circle, Memphis, TN 38125

©All rights reserved. Varco Pruden Buildings® is a division of BlueScope Buildings North America, Inc. Varco Pruden meets or exceeds the most comprehensive testing and compliance standards in the building system industry. To learn more about our products, services and qualifications, visit our website, [www.vp.com](http://www.vp.com). **Building Solutions... one relationship at a time.**

2095 TextureClad Wall  
Issue Date: 2003  
Revised: 10/16